

// GF-TELE JIB

The GF-Tele Jib is a lightweight, stable and variable length Jib Arm. The advantage is a very fast resetting of the arm length by telescoping in or out and then fixing the arm at the required working length. It carries camera packages of up to 45 kg and offers smooth, vibration free movements, added flexibility when working on tight sets. It comes loaded onto one trolley with weights and accessories.



GF-7500 GF-Tele Jib consisting of:

- Adjustable front arm (crankable)
- Crankable counterweight end
- Tilt friction and brakes
- Fitting for double Euro-adapter
- Double Euro-adapter
- 2 counterweight rods



GF-7510 Transport trolley for GF-Tele Jib, 8 counterweights and accessories

TECHNICAL SPECIFICATIONS

Reach - retracted	103 cm / 3'5"
Reach - extended	156 cm / 5'1"
Rear - retracted	37 cm / 1'3"
Rear - extended	54 cm / 1'9"
Max. payload - retracted	45 kg / 99 lbs
Max. payload - extended	30 kg / 66 lbs
Jib mount	Euro-adapter (Mitchell available)
Camera head mount	Euro-adapter to Bowl or Mitchell
Weight of Jib	25 kg / 55 lbs
Max. counterweight	96 kg / 211 lbs [8 x 12 kg]
Tilt angle	56°



Different camera mounting positions