

// GF-JIB

The GF-Jib Arm was designed to function as a stable, solid jib specifically for heavier camera packages up to 60 kg. It comes packed onto one trolley with weights and accessories. Its manual length adjustment allows it to be quickly set at the required length.



GF-7800 GF-Jib consisting of:

- Adjustable front arm
- Crankable counterweight end
- Tilt friction and brakes
- Fitting for double Euro-adapter
- Double Euro-adapter
- 1 counterweight rod



The GF-Jib's counterweight arm is telescopic and can be easily adjusted to the required length with just a few turns of the crank to ensure perfect balance at any angle.



Cameras can be mounted in different positions and the Combi-rig extension tubes provide additional setup possibilities.



GF-7810 Transport trolley for GF-Jib, 10 counterweights and accessories

TECHNICAL SPECIFICATIONS

Reach - retracted	139 cm / 4' 6"	Weight of Jib	42 kg / 92 lbs
Reach - extended	188 cm / 6' 1"	Max. counterweight	120 kg / 264 lbs (10 x 12 kg)
Rear - retracted	42 cm / 1' 4"	Tilt angle	43°
Rear - extended	94 cm / 3' 1"		
Lift range - retracted	186 cm / 6' 1"		
Lift range - extended	256 cm / 8' 4"		
Max. payload - retracted	60 kg / 132 lbs		
Max. payload - extended	40 kg / 88 lbs		
Jib mount	Euro-adapter (Mitchell available)		
Camera head mount	Euro-adapter to Bowl or Mitchell		